

UMBRA AL2500



AL2502

Benefits

- Clean contemporary styling
- High vandal resistance from polycarbonate cylinder

Features

- Cast aluminium base and top cap with spun aluminium canopy, all finished in polyester powder coating
- Aluminium top canopy finished on the inner surface with a reflective white paint
- Impact resistant clear polycarbonate cylinder (UV stabilised)
- Mirrored louvres (AL2501) or circular shield version (AL2502) ensure directional light control and minimal glare
- Integral gear control
- Supplied in Silver (RAL 9006) as standard

Colours

- RAL9006 Silver



AL2501

	Lamp wattage and type	Lamp holder	Description	Weight (Kg)*	Windage (m ²)
AL2501	70/100W HCI-E/P	E27	Mirrored louvre; integral gear	9.1	0.14
AL2501	50/70/100W SON-E	E27/E40	Mirrored louvre; integral gear	9.1	0.14
AL2501	50/80/125W HQL	E27	Mirrored louvre; integral gear	9.2	0.14
AL2501	42W DULUX-T/E	GX 24q-3	Mirrored louvre; integral gear	7.3	0.14
AL2502	70/100W HCI-E/P	E27	Circular shield; integral gear	9.1	0.14
AL2502	50/70/100W SON-E	E27/E40	Circular shield; integral gear	9.1	0.14
AL2502	50/80/125W HQL	E27	Circular shield; integral gear	9.2	0.14
AL2502	42W DULUX-T/E	GX 24q-3	Circular shield; integral gear	7.3	0.14

*Max in range.



Column and bracket options

Choose between fixed and base hinged

	5m	4m		5m	4m
Fixed			Base diameter (mm) Shaft diameter (mm) Base height (mm) Flange plate Root length (mm) Door opening (mm) Cable entry (root) (mm)		
Tubular	TB050	TB040/M741		140/168	140/168
Tubular in silver	TB050/2P9006	TB040/M741/2P9006		76	76
Lo-cone	TB050/LC2	TB040/LC2		1250	1250
Lo-cone in Silver	TB050/LC2/2P9006	TB040/LC2/2P9006		Type 0	Type 0
Base				800	600
Light duty	T051RLS	T041RLS		500 x 100	500 x 100
Light duty in Silver	T051RLS/2P9006	T041RLS/2P9006		150 x 50	150 x 50
For flange plate add /FP: e.g. TB040/FP/LC2					
Accessories					
ELSAB1/6A	Single phase, cut-out, 6A, termination plate				
AL2599	Asymmetric shield (suitable for AL2501 only)				




Columns and brackets finished hot dip galvanised to BSEN1461:1999

Where indicated, columns are spray painted with a long life 2-pack acrylic coat, wet finish 190 microns. RAL9006 Silver.




Key features




Dimensions & Mounting

AL2501
Mounting height: 4m-5m




Maintenance

Access to lamp & gear by removing polycarbonate cylinder



AL3401

70W SON-E
Mounting height: 4m



AL3401

70W SON-E
Mounting height: 4m

All dimensions are in mm.